

Electric Scissor Lifts

# HS18 E PRO



- High performance & rough terrain capacities
- Optional & removable, low fuel consumption Range Extender (Stage 5)
- Multiple charging modes including optional accelerated charge
- Extended duty cycles
- Haulotte Activ'Energy Management takes care of your battery
- Easy access to components
- Activ'Screen: on-board configuration & diagnostic interface
- Maintenance and service-oriented
- Smooth & proportional movements
- Versatile use: outdoor / indoor
- Silent & clean operations
- Full electric drive
- Drive axle with manual locking rear differential increases ground traction
- Oscillating axle delivers excellent ground adherence
- Platform capacity of 750 kg

## TECHNICAL DATA



Working height	18 m
Platform height	16 m
Lift capacity	750 kg (4 pers.)
Platform length	3.82 m
Platform length - extended	5.8 m
Length - extension	0.93 m
Platform width - outside	1.89 m
Height - stowed	3.15 m
Overall width	2.3 m
Length	4.4 m
Wheelbase	2.76 m
Drive speed	5 km/h
Max. drive working height	13m
Gradeability	40 %
Turning radius - outside	6.75 m
Batteries	8 x 6 V - 435 Ah (C20)
Weight	8 010 kg
Tyres	830 x 285 mm
Lift capacity on the extension	225 kg
Height - guardrails lowered	2.29 m
Ground clearance	30.7 cm
Tilt (lonitudinal / lateral)	5° / 2°
XL platform length (option)	4.94 m
XL platform length - extended (option)	7.4 m

## STANDARD EQUIPMENT



- 4 wheel drive
- Mechanical axle with manual locking rear differential
- Front oscillating axle - 6°
- Outriggers with centralized or individual controls
- Dual platform extensions
- Haulotte Activ'Lighting System for safe loading in conditions of low visibility
- Haulotte Activ'Screen
- AC motors
- 48V battery pack
- Haulotte Activ'Energy Management: smart battery management system & manual centralized watering
- Two drop bar entries
- Folding handrails

## MAIN OPTIONS



- Range Extender (5.5 kW - Stage 5)
- Accelerated charger (380 V)
- Haulotte Activ'Energy Management : automatic battery water-filling system
- Platform lighting
- XL platform with dual extensions (7.4 m)
- Double swing gate entries
- AC power to platform plug (110 / 230 V)
- Material handling rack
- Non marking tires
- Cold & arctic weather kits
- Work light
- Scissors stack protection
- Telematics holder & predisposition
- Telematics solutions