

CT36-5A

Gasoline Walk-behind Trowels



**WACKER
NEUSON**
all it takes!



Perfect concrete finishing results

The models of the CT36 trowel range feature a trowel diameter of 915 millimeters - ideal for finishing medium areas. The trowels are optimally balanced, therefore they can be effortlessly controlled in the wide range of speeds. The transmission brake, electronic safety switch and engine speed sensor offer additional triple protection for the user. In an emergency situation the device will simply switch off and the handle will come to a stand-still after no more than a three-quarter turn. Furthermore, the unit will only start if the throttle lever is set to zero. This prevents an inadvertent rotation of the handle on start-up.

- Variable speeds: Low speeds for floating, high speeds for polishing
- Blade pitch up to 30°
- Emergency shutdown

CT36-5A Technical specifications

L x W x H (with handle, fixed version)	2005 x 915 x 1040 mm
Weight (without handle)	73 kg
Troweling diameter	915 mm
Pitch range	0 - 30 °
Rotor speed (min. / max.)	60/125 rpm
Quantity of blades	4
Engine / Motor	Air-cooled single-cylinder four-cycle gasoline engine
Engine / Motor manufacturer	Honda
Engine / Motor type	GX 160
Displacement	165 cm ³
Engine performance (DIN ISO 3046) at rpm	4.3 (5.7) kW (hp) 3,800 rpm
Operating performance (DIN ISO 3046) at rpm	4.3 (5.7) kW (hp) 3,800 rpm
Fuel consumption	1.8 l/h
Tank capacity	3.6 l

Please note: that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions. Subject to alterations and errors excepted. Applicable also to illustrations.

Copyright © 2021 Wacker Neuson SE.