

Product range		DLT 0409			
Type		C35-10	C38	C42	C50
<b>Operational data</b>					
Volume flow <sup>1)</sup>	m <sup>3</sup> /min	3.5	3.8	4.2	5.0
(Optional 9 or 15 kVA Generator)	cfm	123.6	134	148	176.5
Operating pressure	bar	10	7	7	7
	psi	145	101.5	101.5	101.5
<b>Engine</b>		Yanmar 4TNV88C-DCP			
Installed engine power	kW	35.0	35.0	35.0	35.0
RPM-range	rpm	1500 - 2800	1500 - 2800	1500 - 2800	1500 - 2800
<b>Operating weight <sup>2)</sup></b>					
Portable compressor	adjustable towbar braked kg	850 / 785	850 / 785	850 / 785	880 / 825
	adjustable towbar unbraked kg	765 / 730	765 / 730	765 / 730	-
	straight towbar braked kg	810 / 760	810 / 760	810 / 760	840 / 800
	straight towbar unbraked kg	750 / 710	750 / 710	750 / 710	780 / 740
Permissible gross weight	kg	1025 / 750	1025 / 750	1025 / 750	1025 / 750
<b>Filling capacities</b>					
Engine oil	l	6.5	6.5	6.5	6.5
Diesel tank	l	60	60	60	60
Compressor oil	l	9	9	9	9
<b>Dimensions and connections</b>					
Length	adjustable towbar braked mm	3565 - 3910	3565 - 3910	3565 - 3910	3565 - 3910
	straight towbar braked mm	3201	3201	3201	3201
Width	mm	1490	1490	1490	1490
Height (adjustable towbar, braked)	mm	1326	1326	1326	1326
Compressed air outlet		2 x 3/4"			
<b>Sound level</b>					
Sound pressure level <sup>3)</sup>	dB(A) LPA	69	69	69	69