

Product range		DLT 0705				
Type		C55-14	C60-12	C65-10	C65HS	C76
Operational data						
Volume flow ¹⁾	m ³ /min	5.5	6.0	6.5	6.5	7.6
(Optional 9 or 15 kVA Generator)	cfm	194	211.9	229.5	229.5	268
Operating pressure	bar	14	12	10	7	7
	psi	203	174	145	101.5	101.5
Engine		Yanmar 4TNV98CT-NCP				
Installed engine power	kW	53.7	53.7	53.7	53.7	53.7
RPM range	rpm	1500 - 2500	1500 - 2500	1500 - 2500	1500 - 2500	1500 - 2500
Operating weight ²⁾						
Portable compressor	adjustable towbar braked kg	1240	1240	1240	1240	1240
	straight towbar braked kg	1200	1200	1200	1200	1200
Permissible gross weight	kg	1350	1350	1350	1350	1350
Filling capacities						
Engine oil	l	8	8	8	8	8
Diesel tank	l	140	140	140	140	140
Compressor oil	l	17.5	17.5	17.5	17.5	17.5
Dimensions and connections						
Length	adjustable towbar braked mm	3943 - 3974	3943 - 3974	3943 - 3974	3943 - 3974	3943 - 3974
	straight towbar braked mm	3620	3620	3620	3620	3620
Width	mm	1700	1700	1700	1700	1700
Height	mm	1440	1440	1440	1440	1440
Compressed air outlet	3 x 3/4", option to add an extra 1 x 1/2" outlet					
Sound level						
Sound pressure level ³⁾	dB(A) LPA	69	69	69	69	69

¹⁾ Acc. to ISO 1217 Ed. 4 2009 Annex D ²⁾ Operating weight without options ³⁾ Noise level acc. to PNEUROP PN8NTC.2.2 at 7 m